

Low Headroom										
Model	Capacity (ton)	Group Duty (FEM 9.511)	Lifting Height (m)	Lifting Speeds (m/min)	Lifting Motor (kW)	Trolley Speeds (m/min)	Trolley Motor (kW)	Rope Reeving	Rope Diameter (mm)	Weight without counter weight (kg)
CVATB1422TpE315N	3.2	2m	9	4.8 / 0.72	0.4/2.7	14.4 / 4.8	2x 0.1/0.3	4 by 1	8	410
CVATP2512TpE315N	5	2m	7.5	4.8 / 1.2	1.1 / 4.6	14.4 / 4.8	2x 0.1/0.3	4 by 1	10	600
CVATP2522TpE315N	5	2m	11	4.8 / 1.2	1.1 / 4.6	14.4 / 4.8	2x 0.1/0.3	4 by 1	10	600
CVATB3522TpE315N	7	2m	9.5	4.8 / 0.72	1.2 / 9.0	14.4 / 4.8	2x 0.1/0.3	4 by 1	12	615
CVATB3532TpE315N	7	2m	12.5	4.8 / 0.72	1.2 / 9.0	14.4 / 4.8	2x 0.1/0.3	4 by 1	12	615
CVAT4522TpE315N	10	2m	9	4.8 / 1.2	2.0 / 9.6	14.4 / 4.8	2x 0.14/0.44	4 by 1	14	1,010
CVAT5522TpE315N	16	2m	9	4.8 / 1.2	3.6 / 15.6	14.4 / 4.8	2x 0.22/0.66	4 by 1	18	1,535
CVAT5522TpE315N	20 tons	1Am	9	4.8 / 1.2	3.6 / 15.6	14.4 / 4.8	2x 0.22/0.66	4 by 1	18	1,535

Foot Mounted										
Model	Capacity (ton)	Group Duty (FEM 9.511)	Lifting Height (m)	Lifting Speeds (m/min)	Lifting Motor (kW)	Trolley Speeds (m/min)	Trolley Motor (kW)	Rope Reeving	Rope Diameter (mm)	Weight without counter weight (kg)
VATP2512TpE315N	5	2m	7.5	4.8 / 1.2	1.1 / 4.6	n/a	n/a	4 by 1	10	390
VATP2522TpE315N	5	2m	11	4.8 / 1.2	1.1 / 4.6	n/a	n/a	4 by 1	10	425
VATB3522TpE315N	7	2m	9.5	4.8 / 0.72	1.2 / 9.0	n/a	n/a	4 by 1	12	405
VATB3532TpE315N	7	2m	12.5	4.8 / 0.72	1.2 / 9.0	n/a	n/a	4 by 1	12	n/a
VAT4522TpE315N	10	2m	9	4.8 / 1.2	2.0 / 9.6	n/a	n/a	4 by 1	14	685
VAT5522TpE315N	16	2m	9	4.8 / 1.2	3.6 / 15.6	n/a	n/a	4 by 1	18	995
VAT5522TpE315N	20	1Am	9	4.8 / 1.2	3.6 / 15.6	n/a	n/a	4 by 1	18	995
VAT6434TpE315N	30	2m	11.5	3.0 / 0.72	3.6 / 15.6	n/a	n/a	4 by 1	20	1,310